



# TT 052-A II

## ULTRA COMPACT SPEAKER



**Description** The TT 052-A II is an ultra-compact, active speaker designed for high quality indoor near field sound reinforcement. It is equipped with an onboard two-channel 300 W Class-D amplifier. Two powerful 5" neodymium woofers and a 1" compression driver loaded to a constant directivity horn provide optimal coverage. Thanks to the RNet networked control, powerful DSP and proprietary FIRPHASE processing, the TT 052-A II features a 0° linear phase response for TT+ class sound quality.

- Features**
- › 300 W Class D two-channel amplifier
  - › Heavy-duty multi-functional cabinet
  - › 90° conical coverage
  - › FIRPHASE for 0° phase response
  - › 2 x 5" neodymium low distortion woofer
  - › 1.5" c.driver, 1.0" v.c.

<b>Part Number</b>	13000634 TT 052-A II	220-240 V	Black	EAN 8024530017712
	13000635 TT 052-A II	115 V	Black	EAN 8024530017729



# TT 052-A II

## ULTRA COMPACT SPEAKER

		<b>TECHNICAL SPECIFICATIONS</b>	
<b>Acoustical specifications</b>	Frequency Response	65 Hz ÷ 20000 Hz	
	Max SPL @ 1m	123 dB	
	Horizontal coverage angle	90°	
	Vertical coverage angle	90°	
<b>Transducers</b>	Compression Driver	1 x 1.0" neo, 1.5" v.c	
	Woofers	2 x 5.0", 1.0" v.c	
<b>Input/Output section</b>	Input signal	bal/unbal	
	Input connectors	XLR	
	Output connectors	XLR	
	Input sensitivity	-2 dBu/+10 dBu	
<b>Processor section</b>	Crossover Frequencies	1500 Hz	
	Protections	Thermal, Excurs., HF	
	Limiter	Soft Limiter	
	Controls	DSP Controlled RDnet on board	
	RDNet	Yes	
<b>Power section</b>	Total Power	600 W Peak, 300 W RMS	
	High frequencies	300 W Peak, 150 W RMS	
	Low frequencies	300 W Peak, 150 W RMS	
	Cooling	Convection	
	Connections	Powercon IN/OUT	
<b>Standard compliance</b>	Safety agency	CE compliant	
<b>Physical specifications</b>	Cabinet/Case Material	Baltic birch plywood	
	Hardware	Multi-functional	
	Handles	Top, Bottom	
	Grille	Steel	
	Color	Black	
<b>Size</b>	Height	493 mm / 19.41 inches	
	Width	150 mm / 5.91 inches	
	Depth	207 mm / 8.15 inches	
	Weight	9.5 kg / 20.94 lbs	
<b>ACCESSORIES</b>			
<b>Cables</b>	AC XLR 3M3F	13360102	8024530006402
<b>Protections</b>	CVR TT 052	13360170	8024530014063
	AC EB 4X	13360031	8024530018870
<b>Rigging / Mounting</b>	CL-BR TT 051-052	13360171	
	H-BR 2X TT 052	13360205	8024530007508
	PM-KIT TT 051-052	13360172	8024530018658