



GTS 29

HIGH-PERFORMANCE SUBWOOFER



Description

The GTS 29 is a dual 19" subwoofer module for the low-frequency extension in high-demanding touring and install applications, indoors and outdoors. Equipped with two high-excursion best-in-class transducers, it offers excellent playback quality and extreme sound pressure. The cabinet is provided with power connections on front and back panels for easy deployment in cardioid configuration. Up to 16 GTS 29 modules can be fastened on a single fly-bar.

Features

- › 144 dB max SPL
- › 2 x 19" neo woofers, 4" v.c.
- › 3 side handles
- › Designed to operate with XPS 16K amplifier (4 modules per amp unit)
- › Durable and lightweight cabinet construction, polyurea coating
- › Heavy duty, powder coated, custom perforated front grille
- › 2 x 2 P-COM 8 pole bayonet connectors (Gold coated, CA-COM compatible, IP 68)

Part Number

13000820



GTS 29

HIGH-PERFORMANCE SUBWOOFER

Acoustical specifications

Frequency Response (-10dB): 25 Hz ÷ 200 Hz
 Max SPL @ 1m: 144 dB

Power section

Amplification: Full Range
 Nominal Impedance LF: 8 ohm
 Nominal Impedance LF2: 8 ohm

Transducers

Woofer: 2 x 19" neo, 4" v.c.

Input/Output section

Input connectors: P-COM 8POLE
 Output connectors: P-COM 8POLE

Standard compliance

Safety agency: CE compliant

Physical specifications

Cabinet/Case Material: Birch plywood
 Hardware: Suspension Fittings, M20 Socket
 Handles: 3 x side
 Grille: Steel with clothing
 Color: Black

Size

Height: 531.5 mm / 20.93 inches
 Width: 1310 mm / 51.57 inches
 Depth: 735 mm / 28.94 inches
 Weight: 96 kg / 211.64 lbs

Shipping information

Height: 620 mm / 24.41 inches
 Width: 1360 mm / 53.54 inches
 Depth: 800 mm / 31.5 inches
 Weight: 102 kg / 224.87 lbs

Line Art 2D

