



GTS 29

HIGH-PERFORMANCE FLYABLE SUBWOOFER



Description

The GTS 29 is a dual 19" subwoofer module for the low-frequency extension in high-demanding touring and install applications, indoors and outdoors. Equipped with two high-excursion best-in-class transducers, it offers excellent reproduction quality and extreme sound pressure. The cabinet is provided with power connections on front and back panels for easy deployment in cardioid configuration. Up to 16 GTS 29 modules can be ground-stacked or flown on a single fly-bar.

Features

- › 144 dB max SPL
- › 2 x 19" neo woofers, 4" v.c.
- › 3 handles on each side
- › Designed to operate with XPS 16K amplifier (4 modules per amp unit)
- › Tour-tested weather-resistant birch plywood enclosure with durable polyurea coating
- › Heavy-duty, powder-coated, custom perforated front grille
- › 2 Front x 2 Rear P-COM 8 pole bayonet connectors (Gold-plated, CA-COM compatible, IP 68)

Part Number

13000820

GTS 29

Black

EAN 8024530021245



GTS 29

HIGH-PERFORMANCE FLYABLE SUBWOOFER

Acoustical specifications	Frequency Response (-10dB) Max SPL @ 1m	25 Hz ÷ 200 Hz 144 dB
Power section	Amplification Nominal Impedance LF Nominal Impedance LF2	Full Range 8 ohm 8 ohm
Transducers	Woofer	2 x 19" neo, 4.0" v.c
Input/Output section	Input connectors Output connectors	P-COM 8POLE P-COM 8POLE
Standard compliance	Safety agency	CE compliant
Physical specifications	Cabinet/Case Material Hardware Handles Pole mount/Cap Grille Color	Birch plywood Suspension Fittings, M20 Socket 3 x side M20 thread Steel with clothing Black
Size / Weight	Height Width Depth Weight	531.5 mm / 20.93 inches 1310 mm / 51.57 inches 735 mm / 28.94 inches 96 kg / 211.64 lbs

Line Art 2D

