



PD 32A

AC POWER DISTRIBUTION BOX



Description	PD 32A is an AC power distribution box that can distribute power to three XPS 16K amplifiers and auxiliary services. The rackmount chassis is 2RU high. It is powered by a 1.5m long cord equipped with a 32 A CEE 5-pin plug and includes a 32 A CEE 5-pin socket in order to connect energy to a second rack when powered at 230V. The front panel offers one AUX Schuko power inlet and three P-COM 8 connectors as AC power signal distribution for each group of loudspeakers. The back panel offers two powerCON AUX inlets.
Features	<ul style="list-style-type: none">› AC Power for three XPS 16K amplifiers and auxiliary services› Three P-COM 8 connectors› One AUX Schuko power inlet› Two powerCON AUX inlets› 1.5m long cord equipped with a 32 A CEE 5-pin plug› 32A CEE 5-pin socket link› 2RU Rackmount chassis
Part Number	17100016 PD 32A Black EAN 8024530020996



PD 32A

AC POWER DISTRIBUTION BOX

General specifications	Reference standard:	CEI EN 61439-1 (CEI 17-113) CEI EN 61439-2 (CEI 17-114)
	Nominal voltage:	400V
	Nominal current:	32A
	Frequency:	50-60Hz
	Contemporary factor:	0.7
	Power supply:	1 x INPUT via 2m cable with male connector CEE 32A 400V IP44 3P+N+E
	General:	1 x Circuit breaker 4,5kA, 1P+N 10A, C 3 x Circuit breaker 4,5kA, 1P+N 32A, C 6 x INPUT via flying cables with Speakon NL4 connectors 3 x phase signal lamps
	Distribution:	1 x plug CEE OUTPUT 16A 230V 50-60Hz 2P+T 2 x auxiliary connectors AUX - PowerCon NAC3MPB-1 3 x OUTPUT via flying cables with connector PowerCon NAC3FCH 3 x OUTPUT via CA-COM8 1 x plug CEE OUT 32A 230V 50-60Hz 3P+N+T
Standard compliance	IP protection grade	IP 31
	Safety agency	CE compliant
Physical specifications	Cabinet/Case Material	Metal
	Handles	2 x handles for rack mount
	Color	Black
	Rack mounting	19", 2U
Size	Height	88 mm / 3.46 inches
	Width	482 mm / 18.98 inches
	Depth	370 mm / 14.57 inches
	Weight	3.5 kg / 7.72 lbs

Line Art 2D

