GTS 16C

HIGH-PERFORMANCE FLYABLE CARDIOID SUBWOOFER



Description

The GTS 16C is a high-performance flyable cardioid subwoofer, ideal for installations demanding impactful low-frequency performance with controlled dispersion. Built with a high-quality plywood cabinet, it features a 16” neodymium front woofer and a 14” neodymium rear woofer. With integrated suspension hardware, the GTS 16C can be quickly flown or stacked. Equipped with two SpeakON STXX Series 4-pole IP54 heavy-duty metal connectors and capable of cascading up to three modules per XPS 16K channel, it provides reliable and powerful low-frequency output for professional environments.

Features

- 137 dB max SPL
- 16” neodymium woofer
- 14” neodymium rear woofer
- GTX 7C compatible suspension fittings
- 2 Side Handles
- Durable plywood enclosure, polyurea coating
- 2 x SpeakON STXX IP54 heavy-duty metal connectors
- Designed to operate with XPS 16K amplifier (6 subs per amp unit)

Part Number

13000915	GTS 16C	Black	EAN 8024530024666
13001004	GTS 16C W	White	

GTS 16C

HIGH-PERFORMANCE FLYABLE CARDIOID SUBWOOFER

Acoustical specifications	Frequency Response (-10dB)	25 Hz - 200 Hz
	Max SPL @ 1m	137 dB
Power section	Amplification	Full Range
	Nominal Impedance LF	8 ohm
	Nominal Impedance LF Rear (ohm)	8 ohm
	Recommended Amplifiers	XPS 16KD
Transducers	Woofer	1 x 16'' neo, 4.0'' v.c
	Rear Woofer	1 x 14'' neo, 4.0'' v.c
Input/Output section	Input connectors	Speakon® NL4
	Output connectors	Speakon® NL4
Standard compliance	Safety agency	CE compliant
Physical specifications	Cabinet/Case Material	Birch plywood
	Hardware	Suspension Fittings
	Handles	2 x side
	Pole mount/Cap	M20 thread
	Grille	Steel with clothing
	Color	Black, White
Size / Weight	Height	537 mm / 21.14 inches
	Width	605 mm / 23.82 inches
	Depth	777.5 mm / 30.61 inches
	Weight	73 kg / 160.94 lbs

Line Art 2D